



BELT SPECIFICATION
CONVEYOR BELTS

FABREEKA TYPE: 12 PV (WHITE FELT TOP)

DERCO TYPE: 2R/V0-1 NAD

FABRIC	POLYESTER
FILL	RIGID
NUMBER OF PILES	1
TOP COVER	WHITE POLY FELT
TOP COVER THICKNESS	
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
BELT THICKNESS	.106"
WEIGHT PER SQ. FT.	.43 LBS
FOOD QUALITY	FDA
ANTI STATIC	NO
MAXIMUM WIDTH	78-3/4"
WORKING STRENGTH @ 1% ELONGATION	34.3 LBS/INCH
TEMPERATURE RANGE	14 F TO 230 F
MINIMUM PULLEY DIAMETER	1.57"
CO EFFICIENT OF FRICTION	
STEEL	.2
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER SPLICE
PRESS TEMPERATURE	172 C
BELT TEMPERATURE	164 C
	PU FOIL ON BOTTOM
PRESS PRESSURE	30-35 LBS
ALLIGATOR LACE	00
CLIPPER LACE	-----
GATOR LACE	UCM36SP

