



**BELT SPECIFICATION**  
**CONVEYOR BELTS**

**FABREEKA TYPE: 22-75/19 (#19 LONGITUDINAL RIB PROFILE TOP)**

**DERCO TYPE: 2R15 LR-0F 80 OCEAN BLUE**

FABRIC	POLYESTER
FILL	RIGID
TOP COVER	BLUE PVC, #19
PROFILE	
TOP COVER THICKNESS	.059"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
TOTAL BELT THICKNESS	.126"
WEIGHT PER SQ. FT.	.64 LBS
FOOD QUALITY	FDA
ANTI STATIC	YES
MAXIMUM WIDTH	60"
TENSILE STRENGTH	1100 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	60 LBS/INCH
WORKING TEMPERATURE RANGE	-5 F TO 195 F
MINIMUM PULLEY DIAMETER	2"
CO EFFICIENT OF FRICTION	
STEEL	.15
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	<b>FINGER OVER FINGER</b>
ALLIGATOR LACE	7
CLIPPER LACE	UX-1SP
GATOR LACE	OT, 30 LP
VULCANIZER TEMPERATURE	176 C
BELT TEMPERATURE	168 C
	FOIL ON TOP
VULCANIZER PRESSURE	30-35 LBS

