

BELT SPECIFICATION
CONVEYOR BELTS

FABREEKA TYPE: 25-34/1 (#1 NEGATIVE DIAMOND TOP / 80 DUROMETER PVC)

DERCO TYPE: 2LR 6R OF 80 BLACK

FABRIC	POLYESTER
FILL	RIGID
TOP COVER	BLACK PVC, #1
PROFILE	
TOP COVER THICKNESS	.028"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
TOTAL BELT THICKNESS	.086"
WEIGHT PER SQ. FT.	.44 LBS
FOOD QUALITY	NO
ANTI STATIC	YES
MAXIMUM WIDTH	78-3/4"
TENSILE STRENGTH	1100 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	60 LBS/INCH
WORKING TEMPERATURE RANGE	-5 F TO 195 F
MINIMUM PULLEY DIAMETER	1"
CO EFFICIENT OF FRICTION	
STEEL	.15
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER OVER FINGER
VULCANIZER TEMPERATURE	356 F
VULCANIZER PRESSURE	30 LBS
ALLIGATOR LACE	00
CLIPPER LACE	-----
GATOR LACE	UCM36SP

