



**BELT SPECIFICATION**  
**CONVEYOR BELTS**

**FABREEKA TYPE: 28-07**

**DERCO TYPE 2LRFA/FXA1 OF AD**

|                                  |                     |
|----------------------------------|---------------------|
| FABRIC                           | POLYESTER           |
| FILL                             | RIGID               |
| NUMBER OF PILES                  | 2                   |
| TOP COVER                        | FABRIC              |
| TOP COVER THICKNESS              | N/A                 |
| BOTTOM COVER                     | FABRIC, QUIET WEAVE |
| BOTTOM COVER THICKNESS           | N/A                 |
| BELT THICKNESS                   | .063"               |
| WEIGHT PER SQ. FT.               | .32 LBS             |
| FOOD QUALITY                     | NO                  |
| ANTI STATIC                      | YES                 |
| MAXIMUM WIDTH                    | 78-3/4"             |
| TENSILE STRENGTH                 | 1400 LBS/INCH       |
| WORKING STRENGTH @ 1% ELONGATION | 67 LBS/INCH         |
| TEMPERATURE RANGE                | 15 F TO 195 F       |
| MINIMUM PULLEY DIAMETER          | 1.5"                |
| CO EFFICIENT OF FRICTION         |                     |
| STEEL                            | .15                 |
| TYPE BELT SUPPORT                | SLIDER BED          |
| RECOMMENDED SPLICE               | FINGER OVER FINGER  |
| ALLIGATOR LACE                   | 00                  |
| CLIPPER LACE                     | -----               |
| GATOR LACE                       | 25 LL               |
| PRESS TEMPERATURE                | 168 C               |
| BELT TEMPERATURE                 | 160 C               |
| PRESS PRESSURE                   | 35 PSI              |

