

BELT SPECIFICATION
CONVEYOR BELTS

FABREEKA TYPE: U 22-24/A (86 DUROMETER ANTISTATIC WHITE PU)

DERCO TYPE: 2RLH/RA2 1 SPU/PO

FABRIC	POLYESTER
FILL	RIGID
NUMBER OF PLYES	2
TOP COVER	WHITE PU, GLOSS
TOP COVER THICKNESS	.010"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
BELT THICKNESS	.060"
WEIGHT PER SQ. FT.	.34 LBS
FOOD QUALITY	USDA
ANTI STATIC	YES
MAXIMUM WIDTH	78-3/4"
TENSILE STRENGTH	1100 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	60 LBS/INCH
TEMPERATURE RANGE	-5 F TO 212 F
MINIMUM PULLEY DIAMETER	1.18"
CO EFFICIENT OF FRICTION	
STEEL	.15
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER SPLICE
PRESS TEMPERATURE	170 C
BELT TEMPERATURE	159 C
PRESS PRESSURE	30-35 LBS
	2 PCS. FOIL ON TOP
ALLIGATOR LACE	00
CLIPPER LACE	-----
GATOR LACE	25 LL

