



DERCOUSA

BELT SPECIFICATION
CONVEYOR BELTS

FABREEKA TYPE: 25-34 BW (BASKET WEAVE PROFILE / 35 DUROMETER)

DERCO TYPE 2R/RXA 10BW-0 F35 Black

FABRIC	POLYESTER
FILL	RIGID
TOP COVER	35 DURO BLACK
PVC, BASKET	WEAVE PROFILE
TOP COVER THICKNESS	.028"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
TOTAL BELT THICKNESS	.100"
WEIGHT PER SQ. FT.	.55 LBS
FOOD QUALITY	NO
ANTI STATIC	YES
MAXIMUM WIDTH	118"
TENSILE STRENGTH	1100 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	62.8 LBS/INCH – 11 N/MM
WORKING TEMPERATURE RANGE	-5 F TO 195 F
MINIMUM PULLEY DIAMETER	1.58"
CO EFFICIENT OF FRICTION	
STEEL	.15
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER OVER FINGER
ALLIGATOR LACE	1
CLIPPER LACE	UCM36SP
GATOR LACE	OT, 25 L
VULCANIZER TEMPERATURE	176 C
BELT TEMPERATURE	168 C
VULCANIZER PRESSURE	30-35 LBS FOIL ON TOP

