



DERCOUSA

BELT SPECIFICATION
CONVEYOR BELTS

FABREEKA TYPE: 25-11 (80 DUROMETER GREEN PVC X BARE)

DERCO TYPE 2LR 4-8R F80 GREEN

FABRIC	POLYESTER
FILL	RIGID
TOP COVER	GREEN PVC
TOP COVER THICKNESS	.020"
BOTTOM COVER	GREEN PVC, #1
PROFILE	
BOTTOM COVER THICKNESS	.016"
TOTAL BELT THICKNESS	.100"
WEIGHT PER SQ. FT.	.63
FOOD QUALITY	FDA
ANTI STATIC	YES (COVER)
MAXIMUM WIDTH	78-3/4"
TENSILE STRENGTH	900 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	57.1 LBS/INCH – 10 N/MM
WORKING TEMPERATURE RANGE	15 F TO 195 F
MINIMUM PULLEY DIAMETER	1.25"
CO EFFICIENT OF FRICTION	
STEEL	.25
TYPE BELT SUPPORT	SLIDER BED
ROLLER BED	
RECOMMENDED SPLICE	FINGER OVER FINGER
VULCANIZER TEMPERATURE	176 C
BELT TEMPERATURE	167 C
VULCANIZER PRESSURE	30-35 LBS
	FOIL ON TOP & BOTTOM
ALLIGATOR LACE	7
CLIPPER LACE	UCM36SP
GATOR LACE	OT, 30 LP

