



**BELT SPECIFICATION**  
**CONVEYOR BELTS**

**11-11 (80 DUROMETER PVC X NEGATIVE DIAMOND BOTTOM)**

FABRIC	POLYESTER
FILL	FLEXIBLE
TOP COVER	GREEN PVC
TOP COVER THICKNESS	.024"
BOTTOM COVER	GREEN PVC, #1
	PROFILE
BOTTOM COVER THICKNESS	.014"
TOTAL BELT THICKNESS	.0735 "
WEIGHT PER SQ. FT.	.35 LBS
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	YES
MAXIMUM WIDTH	78-3/4"
TENSILE STRENGTH	700 LBS
WORKING STRENGTH @ 1% ELONGATION	60 LBS
WORKING TEMPERATURE RANGE	15 F TO 195 F
MINIMUM PULLEY DIAMETER	1"
CO EFFICIENT OF FRICTION	
STEEL	.25
TYPE BELT SUPPORT	SLIDER BED
	ROLLER BED
RECOMMENDED SPLICE	FINGER SPLICE
PRESS TEMPERATURE	176 F
BELT TEMPERATURE	163 C
PRESS PRESSURE	30-35 LBS
	FOIL ON TOP
ALLIGATOR LACE	00
CLIPPER LACE	UCM36SP

