

**BELT SPECIFICATION**  
**CONVEYOR BELTS**

**11-21 (65 DUROMTER WHITE PVC X NEGATIVE DIAMOND BOTTOM COVER)**

FABRIC	POLYESTER
FILL	FLEXIBLE
NUMBER OF PILES	1
TOP COVER	WHITE PVC
TOP COVER THICKNESS	.024"
BOTTOM COVER	WHITE PVC, # 1
	PROFILE
BOTTOM COVER THICKNESS	.014"
BELT THICKNESS	.0735 "
WEIGHT PER SQ. FT.	.35 LBS
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	NO
MAXIMUM WIDTH	78-3/4"
TENSILE STRENGTH	700 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	60 LBS/INCH
TEMPERATURE RANGE	15 F TO 195 F
MINIMUM PULLEY DIAMETER	1"
CO EFFICIENT OF FRICTION	
STEEL	.25
TYPE BELT SUPPORT	SLIDER BED
	ROLLER BED
RECOMMENDED SPLICE	FINGER SPLICE
PRESS TEMPERATURE	176 C
BELT TEMPERATURE	163 C
PRESS PRESSURE	30-35 LBS
	FOIL IN TOP
ALLIGATOR LACE	00
CLIPPER LACE	-----
GATOR LACE	UCM36SP

