

**BELT SPECIFICATION**  
**CONVEYOR BELTS**

**12-24 (65 DUROMETER PVC)**

|                                  |                  |
|----------------------------------|------------------|
| FABRIC                           | POLYESTER        |
| FILL                             | RIGID            |
| NUMBER OF PILES                  | 1                |
| TOP COVER                        | WHITE PVC, GLOSS |
| TOP COVER THICKNESS              | .019"            |
| BOTTOM COVER                     | FABRIC           |
| BOTTOM COVER THICKNESS           | N/A              |
| BELT THICKNESS                   | .047"            |
| WEIGHT PER SQ. FT.               | .24 LBS          |
| FOOD CONTACT APPROVAL            | FDA              |
| ANTI STATIC                      | NO               |
| MAXIMUM WIDTH                    | 78-3/4"          |
| TENSILE STRENGTH                 | 550 LBS/INCH     |
| WORKING STRENGTH @ 1% ELONGATION | 45 LBS/INCH      |
| TEMPERATURE RANGE                | 25 F TO 175 F    |
| MINIMUM PULLEY DIAMETER          | 3/8" KNIFE EDGE  |
| CO EFFICIENT OF FRICTION         |                  |
| STEEL                            | .15              |
| TYPE BELT SUPPORT                | SLIDER BED       |
| RECOMMENDED SPLICE               | FINGER SPLICE    |
| PRESS TEMPERATURE                | 356 F            |
| PRESS PRESSURE                   | 30 LBS           |
| ALLIGATOR LACE                   | 00               |
| CLIPPER LACE                     | #25 LL           |
| GATOR LACE                       |                  |

