

BELT SPECIFICATION
CONVEYOR BELTS

21-21 (MULTIFILAMENT COVER X NEGATIVE DIAMOND)

FABRIC	POLYESTER
FILL	FLEXIBLE
NUMBER OF PILES	2
TOP COVER	WHITE PVC
TOP COVER THICKNESS	.028"
BOTTOM COVER	WHITE PVC, #1
PROFILE	
BOTTOM COVER THICKNESS	.020"
BELT THICKNESS	.126"
WEIGHT PER SQ. FT.	.72 LBS
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	NO
MAXIMUM WIDTH	78-3/4"
TENSILE STRENGTH	1400 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	110 LBS/INCH
TEMPERATURE RANGE	15 F TO 195 F
MINIMUM PULLEY DIAMETER	2"
CO EFFICIENT OF FRICTION	
STEEL	.25
TYPE BELT SUPPORT	ROLLER BED
SLIDER BED	
RECOMMENDED SPLICE	FINGER OVER FINGER
	7
ALLIGATOR LACE	UX-1SP
CLIPPER LACE	OT, 30 LP
GATOR LACE	
PRESS TEMPERATURE	PRESS- 176 C
	BELT- 166 C
PRESS PRESSURE	30-35psi
	FOIL ON TOP

