

BELT SPECIFICATION
CONVEYOR BELTS

TYPE: 22-07 SI

| | |
|----------------------------------|--|
| FABRIC | POLYESTER |
| FILL | RIGID |
| NUMBER OF PILES | 2 |
| TOP COVER | WHITE SILICONE RUBBER |
| TOP COVER THICKNESS | .010" |
| BOTTOM COVER | FABRIC |
| BOTTOM COVER THICKNESS | N/A |
| BELT THICKNESS | .090" |
| WEIGHT PER SQ. FT. | .46 LBS |
| FOOD CONTACT APPROVAL | FDA |
| ANTI STATIC | NO |
| MAXIMUM WIDTH | 72" |
| TENSILE STRENGTH | 1100 LBS/INCH |
| WORKING STRENGTH @ 1% ELONGATION | 60 LBS/INCH |
| TEMPERATURE RANGE | -100 F TO 350 F |
| MINIMUM PULLEY DIAMETER | 2" |
| CO EFFICIENT OF FRICTION | |
| STEEL | |
| COVER | 2.19 |
| BOTOM | .3 |
| TYPE BELT SUPPORT | SLIDER BED |
| RECOMMENDED SPLICE | FINGER OVER FINGER |
| PRESS TEMPERATURE | 148 C FOR 45 MIN, THEN COOL |
| PRESS PRESSURE | (SI PASTE IN MIDDLE AND TOP) 30 LBS |

