

BELT SPECIFICATION
CONVEYOR BELTS

22-13/6 (#6 PROFILE GREEN SAWTOOTH X NEGATIVE DIAMOND BOTTOM COVER)

FABRIC	POLYESTER
FILL	RIGID
TOP COVER	PVC
TOP COVER THICKNESS	.090"
BOTTOM COVER	PVC,
BOTTOM COVER THICKNESS	.020"
TOTAL BELT THICKNESS	.206"
WEIGHT PER SQ. FT.	.90 LBS
FOOD CONTACT APPROVAL	YES
ANTI STATIC	NO
MAXIMUM WIDTH	78-3/4"
TENSILE STRENGTH	1100 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	60 LBS/INCH
WORKING TEMPERATURE RANGE	15 F TO 195 F
MINIMUM PULLEY DIAMETER	3.15"
CO EFFICIENT OF FRICTION	
STEEL	.25
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER OVER FINGER
VULCANIZER TEMPERATURE	356 F
VULCANIZER PRESSURE	30 LBS
ALLIGATOR LACE	7, 15, 125
CLIPPER LACE	UCM36
GATOR LACE	OT, 1LP

