



BELT SPECIFICATION
CONVEYOR BELTS

22-14 (80 DUROMETER GREEN PVC, COVER X FABRIC)

FABRIC	POLYESTER
FILL	RIGID
TOP COVER	GREEN PVC
TOP COVER THICKNESS	.028"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
TOTAL BELT THICKNESS	.094"
WEIGHT PER SQ. FT.	.58 LBS
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	YES (COVER)
MAXIMUM WIDTH	129"
TENSILE STRENGTH	1100 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	57.1 LBS/INCH
WORKING TEMPERATURE RANGE	5 F TO 194 F
MINIMUM PULLEY DIAMETER	1.57"
CO EFFICIENT OF FRICTION	
STEEL	.18
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER OVER FINGER
VULCANIZER TEMPERATURE	PRESS-176 C BELT-168 C
VULCANIZER PRESSURE	30-35 PSI
ALLIGATOR LACE	1
CLIPPER LACE	-----
GATOR LACE	OT, UCM36SP FOIL ON TOP

