

BELT SPECIFICATION
CONVEYOR BELTS

22-24/4 (#4 SMALL CONE TOP PROFILE, 65 DUROMETER PVC)

FABRIC	POLYESTER
FILL	RIGID
NUMBER OF PILES	2
TOP COVER	WHITE PVC #4
	PROFILE
TOP COVER THICKNESS	.020"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
BELT THICKNESS	.100"
WEIGHT PER SQ. FT.	.74 LBS
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	NO
MAXIMUM WIDTH	80"
TENSILE STRENGTH	1100 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	57.1 LBS/INCH (10 N)
TEMPERATURE RANGE	14 F TO 230 F
MINIMUM PULLEY DIAMETER	1.18"
CO EFFICIENT OF FRICTION	
STEEL	.2
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER OVER
	FINGER
PRESS TEMPERATURE	176 C
BELT TEMPERATURE	166 C
PRESS PRESSURE	30-35 LBS
	FOIL ON TOP
ALLIGATOR LACE	1
CLIPPER LACE	-----
GATOR LACE	OT, UCM36SLSP

