

BELT SPECIFICATION
CONVEYOR BELTS

22-24/5 (#5 NEGATIVE OVAL, 65 DUROMETER PVC)

FABRIC	POLYESTER
FILL	RIGID
NUMBER OF PILES	2
TOP COVER	WHITE PVC, #5
TOP COVER THICKNESS	.028"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
BELT THICKNESS	.113"
WEIGHT PER SQ. FT.	.65 LBS
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	NO
MAXIMUM WIDTH	78-3/4"
TENSILE STRENGTH	1100 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	60 LBS/INCH
TEMPERATURE RANGE	15 F TO 195 F
MINIMUM PULLEY DIAMETER	2"
CO EFFICIENT OF FRICTION	
STEEL	.15
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER OVER FINGER
PRESS TEMPERATURE	356 F
PRESS PRESSURE	30 LBS
ALLIGATOR LACE	1
CLIPPER LACE	-----
GATOR LACE	OT, UCM36SLSP

