

BELT SPECIFICATION
CONVEYOR BELTS

FABREEKA TYPE: 22-24

DERCO TYPE: 2R 7-1 N65 WHITE

FABRIC	POLYESTER
FILL	RIGID
NUMBER OF PILES	2
TOP COVER	WHITE PVC
TOP COVER THICKNESS	.028"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
BELT THICKNESS	.094"
WEIGHT PER SQ. FT.	.54 LBS
FOOD CONTACT APPROVAL	YES
ANTI STATIC	NO
MAXIMUM WIDTH	127"
TENSILE STRENGTH	1100 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	60 LBS/INCH
TEMPERATURE RANGE	15 F TO 195 F
MINIMUM PULLEY DIAMETER	1.58"
CO EFFICIENT OF FRICTION	.15
STEEL	
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER OVER FINGER
PRESS TEMPERATURE	176 C
BELT TEMPERATURE	166 C, FOIL ON TOP
PRESS PRESSURE	30-35 PSI
ALLIGATOR LACE	1
CLIPPER LACE	----
GATOR LACE	OT, UCM36SP

