

BELT SPECIFICATION
CONVEYOR BELTS

22-26/11 (#11 TRACKING GUIDE PROFILE, 65 DUROMETER)

FABRIC	POLYESTER
FILL	RIGID
NUMBER OF PILES	2
TOP COVER	WHITE PVC, # 11
	PROFILE
TOP COVER THICKNESS	.079"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
BELT THICKNESS	.209"
WEIGHT PER SQ. FT.	.93 LBS
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	NO
MAXIMUM WIDTH	48"
TENSILE STRENGTH	1100 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	57.1 LBS/INCH
TEMPERATURE RANGE	14 F TO 230 F
MINIMUM PULLEY DIAMETER	2.36"
CO EFFICIENT OF FRICTION	
STEEL	.2
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER OVER
	FINGER
PRESS TEMPERATURE	176 C
BELT TEMPERATURE	164 C
PRESS PRESSURE	35-40 LBS
	FOIL IN MIDDLE AND
	ON TOP
ALLIGATOR LACE	7
CLIPPER LACE	UCM36SLSP
GATOR LACE	OT, 30 LP

