

BELT SPECIFICATION
CONVEYOR BELTS

22-26/6 (#6 SAWTOOTH PROFILE, 65 DUROMETER)

FABRIC	POLYESTER
FILL	RIGID
NUMBER OF PILES	2
TOP COVER	WHITE PVC, #6
	PROFILE
TOP COVER THICKNESS	.100"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
BELT THICKNESS	.180"
WEIGHT PER SQ. FT.	.90 LBS
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	NO
MAXIMUM WIDTH	78-3/4"
TENSILE STRENGTH	1100 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	60 LBS/INCH
TEMPERATURE RANGE	15 F TO 195 F
MINIMUM PULLEY DIAMETER	2.5"
CO EFFICIENT OF FRICTION	
STEEL	.15
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER OVER FINGER
ALLIGATOR LACE	7
CLIPPER LACE	UCM36SLSP
GATOR LACE	OT, 30 LP
PRESS TEMPERATURE	176C
BELT TEMPERATURE	167 C
PRESS PRESSURE	30 -35 PSI
	FOIL ON TOP

