

BELT SPECIFICATION
CONVEYOR BELTS

22-26/8 (#8 PYRAMID/TRIANGLE PROFILE/FABRIC BOTTOM)

FABRIC	POLYESTER
FILL	RIGID
NUMBER OF PILES	2
TOP COVER	WHITE PVC WITH #8 PROFILE
TOP COVER THICKNESS	.179"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
BELT THICKNESS	.161"
WEIGHT PER SQ. FT.	.93 LBS/SQ.FT
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	NO
MAXIMUM WIDTH	48"
TENSILE STRENGTH	1100 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	57.1 LBS/INCH
TEMPERATURE RANGE	14 F TO 230 F
MINIMUM PULLEY DIAMETER	2.36"
CO EFFICIENT OF FRICTION	
STEEL	
TYPE BELT SUPPORT	.2
RECOMMENDED SPLICE	SLIDER BED FINGER OVER FINGER
PRESS TEMPERATURE	178 C
BELT TEMPERATURE	166 C
PRESS PRESSURE	40 LBS
	2 PCS.OF FOIL ON TOP
ALLIGATOR LACE	7
CLIPPER LACE	UCM36SLSP
GATOR LACE	OT, 30 LP

