

**BELT SPECIFICATION**  
**CONVEYOR BELTS**

**22-45/19 (35 DUROMETER / #19 LONGITUDINAL RIB ON TOP)**

FABRIC	POLYESTER
FILL	RIGID
TOP COVER	GREY COVER, #19
	PROFILE
TOP COVER THICKNESS	.059"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
TOTAL BELT THICKNESS	.126"
WEIGHT PER SQ. FT.	.64 LBS
FOOD CONTACT APPROVAL	NO
ANTI STATIC	YES
MAXIMUM WIDTH	48"
TENSILE STRENGTH	1100 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	60 LBS/INCH
WORKING TEMPERATURE RANGE	-5 F TO 195 F
MINIMUM PULLEY DIAMETER	2"
CO EFFICIENT OF FRICTION	
STEEL	.15
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER OVER FINGER
ALLIGATOR LACE	7
CLIPPER LACE	UCM36
GATOR LACE	OT, 30 LP
VULCANIZER TEMPERATURE	176 C
BELT TEMPERATURE	168 C
VULCANIZER PRESSURE	30-35 PSI
	FOIL ON TOP

