

BELT SPECIFICATION
CONVEYOR BELTS

22-45 (35 DUROMETER LOW NOISE FABRIC)

FABRIC	POLYESTER
FILL	RIGID
TOP COVER	GREY PVC
TOP COVER THICKNESS	.039"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
TOTAL BELT THICKNESS	.106"
WEIGHT PER SQ. FT.	.66 LBS
FOOD CONTACT APPROVAL	NO
ANTI STATIC	YES
MAXIMUM WIDTH	118"
TENSILE STRENGTH	1100 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	62.8 LBS/INCH (11 N)
WORKING TEMPERATURE RANGE	-13 F TO 158 F
MINIMUM PULLEY DIAMETER	1.57"
CO EFFICIENT OF FRICTION	
STEEL	.18
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER OVER FINGER
VULCANIZER TEMPERATURE	356 F
VULCANIZER PRESSURE	30 LBS
ALLIGATOR LACE	7
CLIPPER LACE	UCM36SP
GATOR LACE	OT, 30 LP

