



**BELT SPECIFICATION**  
**CONVEYOR BELTS**

**22-46/3 (35 DUROMETER / #3 ROUGHTOP PROFILE)**

FABRIC	POLYESTER
FILL	RIGID
TOP COVER	GREY PVC, #3
	PROFILE
TOP COVER THICKNESS	.075"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
TOTAL BELT THICKNESS	.201"
WEIGHT PER SQ. FT.	.91 LBS
FOOD CONTACT APPROVAL	NO
ANTI STATIC	YES
MAXIMUM WIDTH	78-3/4"
TENSILE STRENGTH	1100 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	62.8 LBS/INCH
WORKING TEMPERATURE RANGE	-13 F TO 158 F
MINIMUM PULLEY DIAMETER	1.57"
CO EFFICIENT OF FRICTION	
STEEL	.18
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER OVER FINGER
VULCANIZER TEMPERATURE	180 C
BELT TEMPERATURE	170 C
VULCANIZER PRESSURE	40 LBS
	FOIL ON TOP
ALLIGATOR LACE	7, 15, 125
CLIPPER LACE	UCM36
GATOR LACE	OT, 1LP

