



BELT SPECIFICATION
CONVEYOR BELTS

22-75 (80 DUROMETER PVC)

FABRIC	POLYESTER
FILL	RIGID
TOP COVER	BLUE PVC
TOP COVER THICKNESS	.059"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
TOTAL BELT THICKNESS	.126"
WEIGHT PER SQ. FT.	.8 LBS
FOOD CONTACT APPROVAL	NO
ANTI STATIC	YES (COVER)
MAXIMUM WIDTH	127"
TENSILE STRENGTH	1100 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	57.1 LBS/INCH
WORKING TEMPERATURE RANGE	5 F TO 194 F
MINIMUM PULLEY DIAMETER	1.57"
CO EFFICIENT OF FRICTION	
STEEL	.18
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER OVER FINGER
ALLIGATOR LACE	7
CLIPPER LACE	UCM36SLSP
GATOR LACE	OT, 30 LP
VULCANIZER TEMPERATURE	176 C
BELT TEMPERATURE	168 C
VULCANIZER PRESSURE	30-35 psi

