



**BELT SPECIFICATION**  
**CONVEYOR BELTS**

**22-76/3 (#3 ROUGHTOP PROFILE 35 DUROMETER)**

FABRIC	POLYESTER
FILL	RIGID
TOP COVER	BLUE PVC, #3
	PROFILE
TOP COVER THICKNESS	.120"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
TOTAL BELT THICKNESS	.190"
WEIGHT PER SQ. FT.	.9 LBS
FOOD CONTACT APPROVAL	NO
ANTI STATIC	YES
MAXIMUM WIDTH	78-3/4"
TENSILE STRENGTH	1100 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	60 LBS/INCH
WORKING TEMPERATURE RANGE	-5 F TO 195 F
MINIMUM PULLEY DIAMETER	2.36"
CO EFFICIENT OF FRICTION	
STEEL	.15
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER OVER
	FINGER
VULCANIZER TEMPERATURE	356 F
VULCANIZER PRESSURE	30 LBS
ALLIGATOR LACE	7
CLIPPER LACE	UCM36
GATOR LACE	OT, 30 LP

