



DERCOUSA

BELT SPECIFICATION
CONVEYOR BELTS

22-86/8 (#8 65 DUROMETER PYRAMID/TRIANGLE PROFILE/FABRIC BOTTOM)

FABRIC	POLYESTER
FILL	RIGID
NUMBER OF PILES	2
TOP COVER	BLUE PVC WITH #8 PROFILE
TOP COVER THICKNESS	..059"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
BELT THICKNESS	.142"
WEIGHT PER SQ. FT.	.79 LBS/SQ.FT
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	NO
MAXIMUM WIDTH	48"
TENSILE STRENGTH	1100 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	57.1 LBS/INCH
TEMPERATURE RANGE	14 F TO 230 F
MINIMUM PULLEY DIAMETER	2.36"
CO EFFICIENT OF FRICTION	
STEEL	
TYPE BELT SUPPORT	.15
RECOMMENDED SPLICE	SLIDER BED FINGER OVER FINGER
PRESS TEMPERATURE	356 F
PRESS PRESSURE	30 LBS
ALLIGATOR LACE	7
CLIPPER LACE	UCM36SLSP
GATOR LACE	OT, 30 LP

