



**BELT SPECIFICATION**  
**CONVEYOR BELTS**

**25-24/5 (#5 PROFILE NEGATIVE OVAL TOP, 65 DUROMETER)**

FABRIC	POLYESTER
FILL	RIGID
NUMBER OF PILES	2
TOP COVER	WHITE PVC, #5
TOP COVER THICKNESS	.020"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
BELT THICKNESS	.098"
WEIGHT PER SQ. FT.	.60 LBS
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	NO
MAXIMUM WIDTH	78-3/4"
TENSILE STRENGTH	900 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	57.1 LBS/INCH
TEMPERATURE RANGE	14 F TO 230 F
MINIMUM PULLEY DIAMETER	1.18"
CO EFFICIENT OF FRICTION	
STEEL	.2
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER OVER FINGER
ALLIGATOR LACE	1
CLIPPER LACE	-----
GATOR LACE	OT, UCM36SLSP
PRESS TEMPERATURE	176 C
BELT TEMPERATURE	166 C
PRESS PRESSURE	30-35 LBS
	FOIL ON TOP

