

BELT SPECIFICATION
CONVEYOR BELTS

25-24 (65 DUROMETER)

FABRIC	POLYESTER
FILL	RIGID
NUMBER OF PILES	2
TOP COVER	WHITE PVC
TOP COVER THICKNESS	.020"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
BELT THICKNESS	.075"
WEIGHT PER SQ. FT.	.47 LBS
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	NO
MAXIMUM WIDTH	118"
TENSILE STRENGTH	900 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	45 LBS/INCH
TEMPERATURE RANGE	14 F TO 230 F
MINIMUM PULLEY DIAMETER	1.18"
CO EFFICIENT OF FRICTION	
STEEL	.2
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER OVER FINGER
PRESS TEMPERATURE	175 C
BELT TEMPERATURE	165 C
PRESS PRESSURE	FOIL ON TOP 30-35 LBS
ALLIGATOR LACE	00
CLIPPER LACE	-----
GATOR LACE	UCM36SP

