



BELT SPECIFICATION
CONVEYOR BELTS

25-74 (80 DUROMETER PVC)

FABRIC	POLYESTER
FILL	RIGID
TOP COVER	BLUE PVC
TOP COVER THICKNESS	.016"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
TOTAL BELT THICKNESS	.075"
WEIGHT PER SQ. FT.	.47 LBS
FOOD CONTACT APPROVAL	NO
ANTI STATIC	YES
MAXIMUM WIDTH	118"
TENSILE STRENGTH	900 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	45 LBS/INCH
WORKING TEMPERATURE RANGE	-5 F TO 195 F
MINIMUM PULLEY DIAMETER	1"
CO EFFICIENT OF FRICTION	
STEEL	.15
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER OVER FINGER
VULCANIZER TEMPERATURE	176 C
BELT TEMPERATURE	166 C
VULCANIZER PRESSURE	35-40 LBS
ALLIGATOR LACE	00
CLIPPER LACE	-----
GATOR LACE	25 LL FOIL ON TOP

