

BELT SPECIFICATION

CONVEYOR BELTS

2RHA 15-2 PU/PVC (92 DUROMETER CLEAR STAMPING MATERIAL)

PU TOP COVER – PVC INTERLAYER

FABRIC	2 PLY POLYESTER W/ LATERAL STABILITY
FILL	RIGID
TOP COVER	DERPANYL 92 URETHANE
TOP COVER THICKNESS	.059"
BOTTOM COVER	FABRIC, SKIM COATED
BOTTOM COVER THICKNESS	N/A
TOTAL BELT THICKNESS	.146"
WEIGHT PER SQ. FT.	.91 LBS
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	YES
MAXIMUM WIDTH	130"
WORKING STRENGTH @ 1% ELONGATION	57.1 LBS/INCH
WORKING TEMPERATURE RANGE	-4 F TO 212 F
MINIMUM PULLEY DIAMETER	3.93"
CO EFFICIENT OF FRICTION	
STEEL	0.3
TYPE BELT SUPPORT	SLIDER BED ROLLER BED
RECOMMENDED SPLICE	FINGER OVER FINGER
VULCANIZER TEMPERATURE	PRESS -169 C
VULCANIZER PRESSURE	BELT - 160 C 30 PSI FOIL ON TOP OF BELT

