



**BELT SPECIFICATION**  
**CONVEYOR BELTS**

**32-06 (90 DUROMETER CLEAR PVC)**

FABRIC	POLYESTER
FILL	RIGID
NUMBER OF PILES	3
TOP COVER	CLEAR PVC, 90
DUROMETER	
TOP COVER THICKNESS	.079"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
BELT THICKNESS	.191"
WEIGHT PER SQ. FT.	1.22 LBS
FOOD CONTACT APPROVAL	NO
ANTI STATIC	YES (COVER)
MAXIMUM WIDTH	118"
TENSILE STRENGTH	1650 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	135 LBS/INCH
TEMPERATURE RANGE	14 F TO 194 F
MINIMUM PULLEY DIAMETER	3.94"
CO EFFICIENT OF FRICTION	
STEEL	.2
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	TRIPLE FINGER
OVER FINGER	
ALLIGATOR LACE	25, 187
CLIPPER LACE	2
GATOR LACE	1L3P, 3
PRESS TEMPERATURE	170 C
BELT TEMPERATURE	158 C
PRESS PRESSURE	30-35 LBS
	FOIL ON TOP

