

**BELT SPECIFICATION**  
**CONVEYOR BELTS**

**32-11 (80 DUROMETER PVC X NEGATIVE DIAMOND COVER)**

FABRIC	POLYESTER
FILL	RIGID
NUMBER OF PILES	3
TOP COVER	GREEN PVC
TOP COVER THICKNESS	.028"
BOTTOM COVER	GREEN PVC, #1
PROFILE	
BOTTOM COVER THICKNESS	.173"
TOTAL BELT THICKNESS	.169"
WEIGHT PER SQ. FT.	1.08 LBS
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	YES (COVER)
MAXIMUM WIDTH	130"
TENSILE STRENGTH	1650 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	74.2 LBS/INCH
WORKING TEMPERATURE RANGE	5 F TO 194 F
MINIMUM PULLEY DIAMETER	3.15"
CO EFFICIENT OF FRICTION	
STEEL	.35
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	TRIPLE FINGER
VULCANIZER TEMPERATURE	178 C
PRESS TEMPERATURE	167 C
VULCANIZER PRESSURE	30-35 LBS
	FOIL IN MIDDLE & TOP
ALLIGATOR LACE	7
CLIPPER LACE	2, U2
GATOR LACE	30 L

