



**DERCOUSA**

**BELT SPECIFICATION**  
**CONVEYOR BELTS**

**FABREEKA TYPE: 32-46 (35 DUROMETER)**

**DERCO TYPE: 3R 20-0 F35 GRAY**

|                                  |               |
|----------------------------------|---------------|
| FABRIC                           | POLYESTER     |
| FILL                             | RIGID         |
| TOP COVER                        | GREY PVC      |
| TOP COVER THICKNESS              | .079"         |
| BOTTOM COVER                     | FABRIC        |
| BOTTOM COVER THICKNESS           | N/A           |
| TOTAL BELT THICKNESS             | .191"         |
| WEIGHT PER SQ. FT.               | 1.22 LBS      |
| FOOD CONTACT APPROVAL            | NO            |
| ANTI STATIC                      | NO            |
| MAXIMUM WIDTH                    | 118"          |
| TENSILE STRENGTH                 | 1100 LBS/INCH |
| WORKING STRENGTH @ 1% ELONGATION | 74.2 LBS/INCH |
| WORKING TEMPERATURE RANGE        | -5 F TO 195 F |
| MINIMUM PULLEY DIAMETER          | 3.94"         |
| CO EFFICIENT OF FRICTION         |               |
| STEEL                            | .18           |
| TYPE BELT SUPPORT                | SLIDER BED    |
| RECOMMENDED SPLICE               | TRIPLE FINGER |
| VULCANIZER TEMPERATURE           | 356 F         |
| VULCANIZER PRESSURE              | 30 LBS        |
| ALLIGATOR LACE                   | 20, 125       |
| CLIPPER LACE                     | U3            |
| GATOR LACE                       | 1L2P, 2       |

