



BELT SPECIFICATION
CONVEYOR BELTS

32-76 (55 DUROMETER PVC)

FABRIC	POLYESTER
FILL	RIGID
TOP COVER	BLUE GREEN PVC
TOP COVER THICKNESS	.114"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
TOTAL BELT THICKNESS	.226"
WEIGHT PER SQ. FT.	1.3 LBS
FOOD CONTACT APPROVAL	NO
ANTI STATIC	NO
MAXIMUM WIDTH	118"
TENSILE STRENGTH	1100 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	74.2 LBS/INCH
WORKING TEMPERATURE RANGE	14 F TO 230 F
MINIMUM PULLEY DIAMETER	3.15"
CO EFFICIENT OF FRICTION STEEL	.18
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER OVER FINGER
ALLIGATOR LACE	27, 187
CLIPPER LACE	3
GATOR LACE	3, 4.5
VULCANIZER TEMPERATURE	176 C
BELT TEMPERATURE	168 C
VULCANIZER PRESSURE	30-35 PSI

