



DERCOUSA

BELT SPECIFICATION
CONVEYOR BELTS

FABREEKA TYPE: 32-84 (65 DUROMETER)

FABRIC	POLYESTER
FILL	RIGID
NUMBER OF PILES	3
TOP COVER	BLUE PVC
TOP COVER THICKNESS	.028"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
BELT THICKNESS	.140"
WEIGHT PER SQ. FT.	.87 LBS
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	NO
MAXIMUM WIDTH	118"
TENSILE STRENGTH	1650 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	74.2 LBS/INCH – 13 N/MM
TEMPERATURE RANGE	14 F TO 230 F
MINIMUM PULLEY DIAMETER	3.15"
CO EFFICIENT OF FRICTION	
STEEL	.18
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	TRIPLE FINGER
OVER FINGER	
PRESS TEMPERATURE	356 F
PRESS PRESSURE	30 LBS
ALLIGATOR LACE	20, 125
CLIPPER LACE	UCM36LP
GATOR LACE	1L2P, 2

