



BELT SPECIFICATION
CONVEYOR BELTS

33-07i (COTTON POLYESTER FABRIC)

FABRIC	POLYESTER/ COTTON
FILL	FLEXIBLE
NUMBER OF PILES	3
TOP COVER	FABRIC
TOP COVER THICKNESS	N/A
BOTTOM COVER	PVC
IMPREGNATION	
BOTTOM COVER THICKNESS	N/A
BELT THICKNESS	.124"
WEIGHT PER SQ. FT.	.67 LBS
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	NO
MAXIMUM WIDTH	81"
TENSILE STRENGTH	1340 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	40 LBS/INCH
TEMPERATURE RANGE	5 F TO 176 F
MINIMUM PULLEY DIAMETER	2.36"
CO EFFICIENT OF FRICTION	
STEEL	.2
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	TRIPLE FINGER
OVER FINGER	
ALLIGATOR LACE	7
CLIPPER LACE	UCM36
GATOR LACE	OT, 30 LP
PRESS TEMPERATURE	176C
BELT TEMPERATURE	166 C
PRESS PRESSURE	30-35 LBS

