



BELT SPECIFICATION
CONVEYOR BELTS

TYPE: SW 22-07 A

FABRIC	POLYESTER
FILL	RIGID
NUMBER OF PILES	2
TOP COVER	WHITE SILICONE

TOP COVER THICKNESS	.008"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
BELT THICKNESS	.063"
WEIGHT PER SQ. FT.	.33 LBS
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	YES
MAXIMUM WIDTH	80"
TENSILE STRENGTH	1100 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	57.1 LBS/INCH
TEMPERATURE RANGE	-25 F TO 248 F
MINIMUM PULLEY DIAMETER	1.57"

CO EFFICIENT OF FRICTION	
STEEL	.15
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER OVER FINGER/BEVEL
ALLIGATOR LACE	00
CLIPPER LACE	-----
GATOR LACE	25 LL

PRESS TEMPERATURE	172 C
PRESS PRESSURE	25 LBS

PU FOIL ON BOTTOM OF BELT

