

BELT SPECIFICATIONS

U 12-24 A (86 DUROMETER WHITE PU)

FABRIC	POLYESTER
FILL	RIGID
NUMBER OF PLYS	1
TOP COVER	WHITE PU, GLOSS
TOP COVER THICKNESS	.010"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
BELT THICKNESS	.031"
WEIGHT PER SQ. FT.	.16 LBS
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	YES
MAXIMUM WIDTH	78-3/4"
TENSILE STRENGTH	550 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	45 LBS/INCH
TEMPERATURE RANGE	-5 F TO 212 F
MINIMUM PULLEY DIAMETER	3/8" KNIFE EDGE
CO EFFICIENT OF FRICTION STEEL	.15
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER SPLICE
ALLIGATOR LACE	00
CLIPPER LACE	----
GATOR LACE	#25 LL
PRESS TEMPERATURE	170 C
BELT TEMPERATURE	163 C
PRESS PRESSURE	25-30 PSI
	PU FOIL ON TOP

