

BELT SPECIFICATION
CONVEYOR BELTS

U 22-07 A (FABRIC TOP AND ANTISTATIC BOTTOM)

FABRIC	POLYESTER
FILL	RIGID
NUMBER OF PILES	2
TOP COVER	FABRIC
TOP COVER THICKNESS	N/A
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
BELT THICKNESS	.057"
WEIGHT PER SQ. FT.	.32 LBS
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	YES
MAXIMUM WIDTH	78-3/4"
TENSILE STRENGTH	1100 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	60 LBS/INCH
TEMPERATURE RANGE	-15 F TO 212 F
MINIMUM PULLEY DIAMETER	.5"
CO EFFICIENT OF FRICTION	
STEEL	.15
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER OVER FINGER
ALLIGATOR LACE	00
CLIPPER LACE	-----
GATOR LACE	25 LL
PRESS TEMPERATURE	170 C
BELT TEMPERATURE	163 C
PRESS PRESSURE	30-35 LBS

