



BELT SPECIFICATION
CONVEYOR BELTS

U 22-24/1 (#1 NEGATIVE DIAMOND PROFILE, 86 DUROMETER PU)

| | |
|----------------------------------|-------------------------|
| FABRIC | POLYESTER |
| FILL | RIGID |
| NUMBER OF PLYS | 2 |
| TOP COVER | WHITE PU, #1 PROFILE |
| TOP COVER THICKNESS | .027" |
| BOTTOM COVER | FABRIC |
| BOTTOM COVER THICKNESS | N/A |
| BELT THICKNESS | .060" |
| WEIGHT PER SQ. FT | .50 LBS |
| FOOD CONTACT APPROVAL | FDA |
| ANTI STATIC | NO |
| MAXIMUM WIDTH | 78-3/4" |
| TENSILE STRENGTH | 1100 LBS/INCH |
| WORKING STRENGTH @ 1% ELONGATION | 60 LBS/INCH |
| TEMPERATURE RANGE | -5 F TO 212 F |
| MINIMUM PULLEY DIAMETER | 1.5" |
| CO EFFICIENT OF FRICTION | |
| STEEL | .15 |
| TYPE BELT SUPPORT | SLIDER BED |
| RECOMMENDED SPLICE | FINGER SPLICE |
| PRESS TEMPERATURE | 340 F |
| PRESS PRESSURE | 25 LBS |
| ALLIGATOR LACE | 1 |
| CLIPPER LACE | ----- |
| GATOR LACE | OT, UCM36SP |

