



BELT SPECIFICATION
CONVEYOR BELTS

U 22-24/5 (#5 NEGATIVE OVAL / 86 DUROMETER PU)

FABRIC	POLYESTER
FILL	RIGID
NUMBER OF PLYS	2
TOP COVER	WHITE PU, #5
TOP COVER THICKNESS	.016"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
BELT THICKNESS	.081"
WEIGHT PER SQ. FT.	.40 LBS
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	NO
MAXIMUM WIDTH	78-3/4"
TENSILE STRENGTH	1100 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	57.1 LBS/INCH
TEMPERATURE RANGE	-40 F TO 212 F
MINIMUM PULLEY DIAMETER	1.57"
CO EFFICIENT OF FRICTION	
STEEL	.2
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER SPLICE
ALLIGATOR LACE	00
CLIPPER LACE	-----
GATOR LACE	UCM36SP
PRESS TEMPERATURE	172 C
BELT TEMPERATURE	164 C
PRESS PRESSURE	30-35LB
	FOIL ON TOP

