

BELT SPECIFICATION
CONVEYOR BELTS

U 25-24/0FF (86 DUROMETER WHITE PU W/ MATTE FINISH AND FRAYLESS FABRIC)

FABRIC	POLYESTER
FILL	RIGID
NUMBER OF PLYS	2
TOP COVER	WHITE PU, MATTE
TOP COVER THICKNESS	.010"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
BELT THICKNESS	.050"
WEIGHT PER SQ. FT.	.35 LBS.
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	NO
MAXIMUM WIDTH	78-3/4"
TENSILE STRENGTH	900 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	56 LBS/INCH
TEMPERATURE RANGE	-5 F TO 212 F
MINIMUM PULLEY DIAMETER	3/8" KNIFE EDGE
CO EFFICIENT OF FRICTION	
STEEL	.15
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER SPLICE
PRESS TEMPERATURE	340 F
PRESS PRESSURE	25 LBS
ALLIGATOR LACE	00
CLIPPER LACE	-----
GATOR LACE	25 LL

