

BELT SPECIFICATION
CONVEYOR BELTS

UM 25-24 A FF (86 DUROMETER ANTISTATIC FRAYLESS WHITE PU)

FABRIC	POLYESTER
FILL	RIGID
NUMBER OF PLIES	2
TOP COVER	WHITE PU, MATTE
TOP COVER THICKNESS	.008"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
BELT THICKNESS	.055"
WEIGHT PER SQ. FT.	.32 LBS
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	YES
MAXIMUM WIDTH	78-3/4"
TENSILE STRENGTH	900 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	57.1 LBS/INCH
TEMPERATURE RANGE	-4 F TO 212 F
MINIMUM PULLEY DIAMETER	.79"
CO EFFICIENT OF FRICTION	
STEEL	.25
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER SPLICE
ALLIGATOR LACE	00
CLIPPER LACE	-----
GATOR LACE	25 LL
PRESS TEMPERATURE	172 C
BELT TEMPERATURE	164 C
PRESS PRESSURE	40 PSI
	FOIL ON TOP

