



BELT SPECIFICATION
CONVEYOR BELTS

FABREEKA TYPE: U 25-24FF (86 DUROMTER FRAYLESS FABRIC PU)

DERCO TYPE: 2RFL 2-1 SPU/PO WHITE

| | |
|--|-----------------|
| FABRIC | POLYESTER |
| FILL | RIGID |
| NUMBER OF PLYS | 2 |
| TOP COVER | WHITE PU, GLOSS |
| TOP COVER THICKNESS | .010" |
| BOTTOM COVER | FREYLESS FABRIC |
| BOTTOM COVER THICKNESS | N/A |
| BELT THICKNESS | .050" |
| WEIGHT PER SQ. FT. | .35 LBS |
| FOOD CONTACT APPROVAL | FDA |
| BOTH ANTISTATIC AND NON-ANTISTATIC AVAILABLE, PLEASE SPECIFY PREFERENCE | |
| MAXIMUM WIDTH | 78-3/4" |
| TENSILE STRENGTH | 900 LBS/INCH |
| WORKING STRENGTH @ 1% ELONGATION | 56 LBS/INCH |
| TEMPERATURE RANGE | -4 F TO 212 F |
| MINIMUM PULLEY DIAMETER | 3/8" KNIFE EDGE |
| CO EFFICIENT OF FRICTION | |
| STEEL | .15 |
| TYPE BELT SUPPORT | SLIDER BED |
| RECOMMENDED SPLICE | FINGER SPLICE |
| ALLIGATOR LACE | 00 |
| CLIPPER LACE | ----- |
| GATOR LACE | 25 LL |
| | |
| PRESS TEMPERATURE | 170 C |
| BELT TEMPERATURE | 164 C |
| PRESS PRESSURE | 30-35 PSI |
| | FOIL ON TOP |

