

BELT SPECIFICATION
CONVEYOR BELTS

UG27-28/0 (92 DUROMETER COVER X COVER WHITE PU)

FABRIC	POLYESTER
FILL	INTERWOVEN
	MONOFILAMENT
NUMBER OF PLIES	2
TOP COVER	WHITE PU, GLOSS
TOP COVER THICKNESS	.020"
BOTTOM COVER	WHITE PU, MATTE
BOTTOM COVER THICKNESS	.016"
BELT THICKNESS	.081"
WEIGHT PER SQ. FT.	.46 LBS
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	YES
MAXIMUM WIDTH	78"
RECOMMENDED PRE-TENSION	6-12 N/mm
	(STRETCH 0.4-0.7%)
TENSION FOR 1% ELONGATION	97.1 LBS/INCH (17 N)
TEMPERATURE RANGE	-4 F TO 212F
MINIMUM PULLEY DIAMETER	1.57"
CO EFFICIENT OF FRICTION	
STEEL	.5
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER SPLICE
ALLIGATOR LACE	00
CLIPPER LACE	-----
GATOR LACE	25 LL
PRESS TEMPERATURE	170 C
PRESS PRESSURE	30-35 LBS

