

BELT SPECIFICATION
CONVEYOR BELTS

UM32-26 (92 DUROMETER 3 PLY WHITE PU W/ MATTE FINISH)

FABRIC	POLYESTER
FILL	RIGID
TOP COVER	WHITE PU, MATTE
TOP COVER THICKNESS	.039"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
TOTAL BELT THICKNESS	.120"
WEIGHT PER SQ. FT.	1 LBS
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	NO
MAXIMUM WIDTH	78-3/4"
TENSILE STRENGTH	1100 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	74.2 LBS/INCH
WORKING TEMPERATURE RANGE	-4 F TO 212 F
MINIMUM PULLEY DIAMETER	3.15"
CO EFFICIENT OF FRICTION	
STEEL	.15
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER SPLICE
ALLIGATOR LACE	7
CLIPPER LACE	UCM36
GATOR LACE	OT, 30 LP
VULCANIZER TEMPERATURE	172 C
BELT TEMPERATURE	164 C
VULCANIZER PRESSURE	30-35PSI
	FOIL ON TOP

