



DERCOUSA

BELT SPECIFICATION
CONVEYOR BELTS

UM 22-06 (92 DUROMETER PU, MATTE FINISH TOP)

FABRIC	POLYESTER
FILL	RIGID
NUMBER OF PILES	2
TOP COVER	CLEAR PU, MATTE
TOP COVER THICKNESS	.052"
BOTTOM COVER	FABRIC
BOTTOM COVER THICKNESS	N/A
BELT THICKNESS	.091"
WEIGHT PER SQ. FT.	.55 LBS
FOOD CONTACT APPROVAL	FDA
ANTI STATIC	NO
MAXIMUM WIDTH	78-3/4"
TENSILE STRENGTH	1100 LBS/INCH
WORKING STRENGTH @ 1% ELONGATION	60 LBS/INCH
TEMPERATURE RANGE	-5 F TO 212 F
MINIMUM PULLEY DIAMETER	1.5"
CO EFFICIENT OF FRICTION	
STEEL	.15
TYPE BELT SUPPORT	SLIDER BED
RECOMMENDED SPLICE	FINGER SPLICE
PRESS TEMPERATURE	168 C
BELT TEMPERATURE	155 C
	FOIL ON TOP
PRESS PRESSURE	25 LBS
ALLIGATOR LACE	1
CLIPPER LACE	----
GATOR LACE	OT, UCM36SP

