



## **2 PLY HYTREL WITH WAVY TOP**

<b>COVER</b>	<b>92 SURE A HYTREL</b>
<b>COLOR</b>	<b>NATURAL</b>
<b>PLIES</b>	<b>2 (CROSS RIGID)</b>
<b>WEIGHT (LBS. SQ. FT.)</b>	<b>.52</b>
<b>OVERALL GAUGE (INCHES)</b>	<b>.150"</b>
<b>TOP COVER THICKNESS</b>	<b>.039"</b>
<b>ANTISTATIC FABRICATION</b>	<b>YES</b>
<b>TENSILE FORCE FOR 1% STRAIN</b>	<b>10 N/MM</b>
<b>RECOMMENDED TENSION (STRAIN)</b>	<b>.4-.7%</b>
<b>MINIMUM PULLEY DIAMETER (INCHES)</b>	<b>1.97"</b>
<b>TEMPERATURE RANGE (°F)</b>	<b>-40 to +212</b>
<b>MEETS FDA REQUIREMENTS</b>	<b>YES</b>
<b>APPROVED FOR TOBACCO USE</b>	<b>MEETS AND/OR EXCEEDS ALL REQUIREMENTS FOR DIRECT CONTACT WITH TOBACCO</b>
<b>COVER SURFACE CONFIGURATION</b>	<b>WAVY TOP PROFILE</b>
<b>BOTTOM SURFACE CONFIGURATION</b>	<b>BARE</b>
<b>COEFFICIENT OF FRICTION BOTTOM SURFACE</b>	<b><u>STEEL</u> 0.20</b>