



## **2 PLY NR ROUGHTOP**

<b>BELT</b>	<b>FABREEKA TOBACCO</b>
<b>TYPE</b>	<b>ROUGHTOP</b>
<b>COLOR</b>	<b>TAN</b>
<b>PLIES</b>	<b>2</b>
<b>WEIGHT (LBS. SQ. FT.)</b>	<b>1.50</b>
<b>AVAILABLE WIDTH (INCHES)</b>	<b>54 TO 72</b>
<b>OVERALL GAUGE (INCHES)</b>	<b>0.281 +/- 0 .015</b>
<b>TENSILE STRENGTH (LBS./IN. Of WIDTH)</b>	<b>1500</b>
<b>RECOMMENDED WORKING TENSION (LBS./IN. OF WIDTH)</b>	<b>150</b>
<b>MINIMUM PULLEY DIAMETER (INCHES)</b>	<b>4</b>
<b>TEMPERATURE RANGE (°F)</b>	<b>0 TO 180</b>
<b>APPROVED FOR TOBACCO USE</b>	<b>MEETS AND/OR EXCEEDS REQUIREMENTS FOR DIRECT CONTACT WITH TOBACCO.</b>
<b>MEETS FDA REQUIREMENTS</b>	<b>YES</b>
<b>MAJOR POLYMER CONTENT</b>	<b>NATURAL RUBBER COVER</b>
<b>COVER SURFACE CONFIGURATION</b>	<b>ROUGHTOP</b>
<b>BOTTOM SURFACE CONFIGURATION</b>	<b>BARE/STRIKE THRU</b>
<b>COEFFICIENT OF FRICTION</b>	<b><u>STEEL</u>   <u>CARDBOARD</u></b>
<b>COVER SURFACE</b>	<b>N/A   N/A</b>
<b>BOTTOM SURFACE</b>	<b>.20   0.40</b>
<b>TYPICAL END-USE APPLICATION</b>	<b>CONVEYING CARTONS UP AN INCLINE</b>