



### **3 PLY BRITE TDL**

<b>BELT</b>	<b>FABREEKA BRITE TOBACCO</b>
<b>TYPE</b>	<b>FLAT SURFACE</b>
<b>COLOR</b>	<b>NATURAL</b>
<b>PLIES</b>	<b>3</b>
<b>WEIGHT (LBS. SQ. FT.)</b>	<b>0.4</b>
<b>AVAILABLE WIDTH (INCHES)</b>	<b>72</b>
<b>OVERALL GAUGE (INCHES)</b>	<b>0.065 +/- 0.010</b>
<b>TENSILE STRENGTH (LBS./IN. OF WIDTH)</b>	<b>380</b>
<b>RECOMMENDED WORKING TENSION (LBS./IN. OF WIDTH)</b>	<b>30</b>
<b>MINIMUM PULLEY DIAMETER (INCHES)</b>	<b>1</b>
<b>TEMPERATURE RANGE (°F)</b>	<b>-40 to +250</b>
<b>MEETS FDA REQUIREMENTS</b>	<b>YES</b>
<b>APPROVED FOR TOBACCO USE</b>	<b>MEETS AND/OR EXCEEDS ALL REQUIREMENTS FOR DIRECT CONTACT WITH TOBACCO</b>
<b>MAJOR POLYMER CONTENT</b>	<b>NATURAL</b>
<b>COVER SURFACE CONFIGURATION</b>	<b>BARE</b>
<b>BOTTOM SURFACE CONFIGURATION</b>	<b>BARE</b>
<b>COEFFICIENT OF FRICTION</b>	<b><u>STEEL</u>   <u>CARDBOARD</u></b>
<b>COVER SURFACE</b>	<b>0.20   0.35</b>
<b>BOTTOM SURFACE</b>	<b>0.20   0.35</b>
<b>TYPICAL END-USE APPLICATION</b>	<b>HORIZONTAL CONVEYING</b>